


Mod. 3005 D

COPOLYMER POLYPROPYLENE WATERPROOF CASE



Metric mm-Kg-C°



INTERNAL DIMENSIONS

L Length	300 mm
W Width	210 mm
D Depth	58 mm
Lid	20 mm
Base	38 mm


EXTERNAL DIMENSIONS

L Length	326 mm
W Width	269 mm
D Depth	75 mm

OTHER DATA

Empty weight	1,10 Kg
Weight with foam	1,20 Kg
Weight with brings rifles	Kg
Volume	4 lt
Buoyancy	2,10 Kg/max
Operating temperature	°C min +90 / max -33

Imperial in-lbs-F°



INTERNAL DIMENSIONS

L Length	11 13/16 in
W Width	8 1/4 in
D Depth	2 5/16 in
Lid	0 13/16 in
Base	1 1/2 in

EXTERNAL DIMENSIONS

L Length	12 13/16 in
W Width	10 9/16 in
D Depth	2 15/16 in

OTHER DATA

Empty weight	2.42 lbs
Weight with foam	2.64 lbs
Weight with brings rifles	lbs
Volume	0.95 gal
Buoyancy	4.62 lbs/max
Operating temperature	°F min +194 / max -27.4

Mod. 3005 D

ACCESSORIES



PATENTED COMBINATION PADLOCK

Designed to fit snug to the Explorer case mould so as not to swing out



PATENTED HEAVY DUTY BRASS PADLOCK WITH KEYS

Designed to fit snug to the Explorer case mould so as not to swing out



TSA APPROVED PADLOCK WITH COMBINATION

The new TSA approved padlocks allow tsa® airport security agents to open the case without destroying the lock. TSA agents are trained to recognize the travel sentry certified logo and should not break the case lock.



FOAM SET FOR CASE 3005

Layers of pre cubed foam for the bottom and convoluted foam for the lid



BLIND INSERT

Kit includes 6 pcs.

Whenever the slots are not going to be used for in-built applications, those can be closed by blind inserts that will give the case a better and finished interior look.



METAL BRACKET

Kit includes 6 pcs.

All models (except for the 1908) are internally equipped with specific slots, to apply the optional metal or plastic brackets which provide either a panel's fixing points or a fix mechanical joint inside the case, to build more complete applications. This way the case becomes a real workstation, rather than just a carrying container. As the panel mounting brackets are mechanically fixed by screws, they can be removed when necessary. The dedicated screws allow the case to remain waterproof, and help the panels to be removed easily and quickly



PLASTIC BRACKET

Kit includes 6 pcs.

All models (except for the 1908) are internally equipped with specific slots, to apply the optional metal or plastic brackets which provide either a panel's fixing points or a fix mechanical joint inside the case, to build more complete applications. This way the case becomes a real workstation, rather than just a carrying container. As the panel mounting brackets are mechanically fixed by screws, they can be removed when necessary. The dedicated screws allow the case to remain waterproof, and help the panels to be removed easily and quickly

CONVOLUTED FOAM SET FOR CASE 3005

(includes 2 pcs.)



FEATURES



(in certain models)



Internal slots for optional panel mounting brackets or panel mounting rings



The internal stop ring prevents valve from being completely extracted (Art. PURGEVALVE.B)



(Art. LABELCOVER + nr. art.)



(Art. NEOSEAL + nr. art.)